

BENNY

Specifications

Mechanism or structure: High resistance steel tube epoxy baked painted. Orthopedic bed with quality continental weld-mesh (sofabed only), fixed to the frame with springs. Comfortable seating made with webbing. Opening and closing operations with two simple movements (sofabed only).

Mattress standard (sofabed only): Interior Bonnel springing made of a Ø 2,00 mm. hardened steel; CM expanded polyurethane foam 27 Kg/m³; cover in 100% CO ecru FR treated fabric quilted with FR 100% PL 200 g/m² and non woven support; sides in 100% CO ecru FR treated fabric quilted with mm. 5 foam and non woven support; FR piping. The mattress meets the requirement of BS 7177 : 2011 Specification for Resistance to ignition of Mattresses, Divans and Bed Bases for "Low Hazard".

Frame: solid fir, poplar plywood and poplar multilayer.

Legs: Metal chrome finish.

Padding:

Seat: expanded polyurethane foam CMHR 35 Kg/m³ covered with feather + down and interliner. **Back:** expanded polyurethane CM foam 25 Kg/m³ with different compression loads; needle-punched thermo-fixed fiber 280 g/m² combined with Schedule 3 interliner and 2,5 mm. quilted interliner, covered with feather + down and interliner. **Side arm cushions:** expanded polyurethane CM foam 25 kg/m³ covered with 200 g/m² PL fibre, feather + down and interliner. **Frame:** Expanded polyurethane foam ELAST 65 Kg/m³ + 40 Kg/m³ CM, covered with needle-punched thermo-fixed fiber TL/S-C 200 gr/m² combined with Schedule 3 interliner and 2,5 mm. foam combined interliner.

Fabric: Specifications: see sample attached.

All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Saety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

We suggest not to sit on armrests.

MADE IN ITALY