

DAVE

Specifications

<u>Mechanism</u> (sofa bed): high-strength cold drawn steel tube, painted with epoxy powder, two folds, front opening in two movements by extraction of the seat. Orthopedic bed with beech wood slats. Seat made with webbing.

<u>Mattress standard</u> (sofa bed only): Expanded polyurethane foam 35 Kg/m³ CMHR covered on both sides with FR treated 100% cotton fabric quilted with 100% polyester fiber 200 g/m² and non-woven.

Frame: Solid fir, poplar multilayer, hardboard.

Legs: polished aluminum.

<u>Padding</u>: Seat: feather + down and interliner with expanded polyurethane foam 35 Kg/m 3 . Back cushions: feather + down and interliner. Frame: expanded polyurethane foam 25 and 40 Kg/m 3 ; resinated polyester fiber 200 gr./m 2 combined with interliner.

Fabric: Specifications: see sample attached.

All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Saety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

We suggest not to sit on armrests.

MADE IN ITALY