

DENNIS

Specifications

Frame: multilayer of poplar wood.

Padding:

Seat: feather + down and interliner and expanded polyurethane foam CMHR 35 Kg/m³ and needle-punched thermo-fixed fiber 200 g/m² combined with Schedule 3 interliner and 2,5 mm. quilted interliner. **Feather + down back cushions:** feather + down and interliner. **Foam back cushion (option):** expanded polyurethane foam covered with resinated polyester fiber 400 g/m² and needle-punched thermo-fixed fiber 380 g/m². **Frame:** 10 mm. CM foam combined with Schedule 3 interliner and 2,5 mm. foam combined interliner. **Headboard and armrest:** Expanded polyurethane foam 40 Kg/m³ PCM and 10 mm. CM foam combined with Schedule 3 interliner and 2,5 mm. foam combined interliner.

Legs: ABS, Hytrel Du Pont

Wheels: Nylon, ABS, Hytrel Du Pont

Hinge: aluminium

Hook and locking plates: galvanized metal

Fabric: Specifications: see sample attached.

All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Safety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

It's absolutely forbidden to sit on headboards and armrests.

MADE IN ITALY