

## ELLINGTON

### *Specifications*

#### **Mechanism or structure:**

High resistance steel tube epoxy baked painted. Orthopedic bed with beech wood slats. Seat made with webbing. Opening and closing operations with one single movement (sofabed only).

#### **Mattress standard** (sofabed only):

Expanded polyurethane foam CMHRP 35 Kg/m<sup>3</sup>; cover 100% CO, quilted with 100% PL gr. 200/m<sup>2</sup>  
Flame test: The Furniture and Furnishing (Fire) (Safety) Regulation 1988 S.I. N. 1324 BS 5852 Part 2 Crib 5;

#### **Frame:**

Back: high resistance steel tube epoxy baked painted. Armrests: solid fir, particle wood and poplar plywood. Headboard: solid fir and particle wood. Front panel multi-layer of poplar wood.

#### **Padding:**

**Seat:** expanded polyurethane foam 35 Kg/m<sup>3</sup> covered with needle-punched thermo-fixed fiber TL/S-C 200 gr/m<sup>2</sup> combined with Schedule 3 interliner and 2,5 mm. foam combined interliner.

**Back:** expanded polyurethane foam 25 Kg/m<sup>3</sup> covered with needle-punched thermo-fixed fiber TL/S-C 300 gr/m<sup>2</sup> combined with Schedule 3 interliner and 2,5 mm. foam combined interliner.

**Armrests and frame:** expanded polyurethane foam 40 kg/m<sup>3</sup>, covered with Schedule 3 interliner combined with 200 g/m<sup>2</sup> PL fibre.

#### **Fabric:**

Specifications: see sample attached. All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Safety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

*We suggest not to sit on armrests.*

MADE IN ITALY