

FREDDIE

Specifications

Mechanism (sofabed): high-strength cold drawn steel tube, painted with epoxy powder, two folds, front opening in two movements by extraction of the seat. Orthopedic bed with beech wood slats. Seat made with webbing.

Standard CMS BS mattress (sofabed only): Expanded polyurethane foam 35 Kg/m³ CMHR covered on both sides with FR treated 100% cotton fabric quilted with 100% polyester fiber 200 g/m² and non-woven.

→ *The mattress meets the requirement of BS 7177 : 2011 Specification for Resistance to ignition of Mattresses, Divans and Bed Bases for "Low Hazard".*

→ *The mattress meets the requirements CPSC 16 CFR Part 1633:2011 - Standard for the flammability (open flame) of mattress set.*

Frame: solid fir and hardboard.

Padding: Seat: expanded polyurethane foam 35/N Kg/m³ CMHR; needle-punched thermo-fixed fiber 200 gr/m² covered with Schedule 3 interliner and 2,5 mm. foam combined interliner. **Back:** expanded polyurethane foam 25/M Kg/m³ CM; needle-punched thermo-fixed fiber 300 gr/m² covered with Schedule 3 interliner. **Structure:** expanded polyurethane foam 40/P and 25 Kg/m³ CM covered with resinated polyester fiber 200 gr/m² combined with Schedule 3 interliner and 2,5 mm. foam combined interliner.

Legs: metal epoxy baked painted.

Fabric: Specifications: see sample attached. All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Safty) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

We suggest not to sit on armrests and headboard.

MADE IN ITALY