

# GARRISON GARRISON-2

## Specifications

### Mechanism (for bed only)

High resistance steel tube epoxy baked painted. Orthopedic bed with quality continental weld-mesh, fixed to the frame with springs. Seating with webbings. Opening and closing operations with two movements.

### Mattress (for bed only)

Expanded polyurethane foam 35 Kg/m<sup>3</sup> CMHR covered on both sides with FR treated 100% cotton fabric quilted with 100% polyester fiber 400 g/m<sup>2</sup> and non-woven.

The mattress meets the requirement of BS 7177 : 1996 Specification for Resistance to ignition of Mattresses, Divans and Bed Bases.

### Frame

Solid fir, poplar plywood.

### Seat frame (for sofa without bed)

Solid fir, webbings.

### Legs

Metal black chrome finish.

### Padding

**Seat:** feather + down and interliner; expanded polyurethane foam 35 Kg/m<sup>3</sup> CMHR; needle-punched thermo-fixed fiber 300 gr/m<sup>2</sup> covered with Schedule 3 interliner and 2,5 mm. foam combined interliner.

**Back:** feather + down and expanded polyurethane foam 25 Kg/m<sup>3</sup> CMC; covered with interliner.

**Frame:** expanded polyurethane foam ELAST 65 Kg/m<sup>3</sup> + 40 Kg/m<sup>3</sup> CM, covered with resinated polyester fiber 200 gr/m<sup>2</sup> combined with Schedule 3 interliner and 2,5 mm. foam combined interliner.

### Fabric

Specifications: see sample attached. All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Saety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

*We suggest not to sit on armrests.*

MADE IN ITALY