

GEORGE

Specifications

Mechanism: High resistance steel tube – epoxy baked painting. Orthopaedic bed with beech wood slats.

Standard mattresses: Expanded polyurethane CMHRP 35 Kg/m³; top cover 100% CO quilted with 100% PL fibre 200 g/m²; covered underneath with an interliner, combined with 2,5 mm. foam. Sides in 100% CO fabric, quilted with polyurethane foam. The mattress meets the requirement of BS 7177 : 2008 Specification for Resistance to ignition of Mattresses, Divans and Bed Bases – Low Hazard.

Padding: Back: Expanded polyurethane foam, 25 Kg/m³ covered with 2,5 mm. combined interliner. **Back cushions:** Expanded polyurethane foam 25 Kg/m³ covered with needle-punched thermo-fixed fiber TL/S-C 300 gr/m² combined with Schedule 3 interliner. **Frame:** 10 mm. foam combined with interliner

Bedspread: bottom: 100% cotton fabric FR treated; padding: FR resinated 100% polyester fiber "Valform" 100 gr/m²; top: Schedule 3 interliner.

Fabric: Specifications: see sample attached. All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Saety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

MADE IN ITALY