

JACK JACK-CLASSIC

Specifications

Mechanism: High resistance steel tube – epoxy baked painting. Orthopedic bed with beech wood slats. Bottom panel (optional): particle wood covered with melamine.

Mattress (standard): Expanded polyurethane foam, 27 Kg/m³ CM; covered on top with 100% FR cotton fabric, bottom with 2,5 mm. combined interliner.

Frame: Front, back and side panels, Jack armrests, headboard: particle wood. Jack-Classic armrests in solid fir, particle wood and hardboard.

Padding: Structure: 10 mm. CM foam combined with Schedule 3 interliner and 2,5 mm. foam combined interliner. Jack-Classic armrests: Expanded polyurethane foam 40 Kg/m³ PCM and 10 mm. CM foam combined with Schedule 3 interliner and 2,5 mm. foam combined interliner. Back cushions: Expanded polyurethane foam 25 Kg/m³ covered with needle-punched thermo-fixed fiber TL/S-C 300 gr/m² combined with Schedule 3 interliner. Bolster pillows (option): 100% anti-allergic polyester flock covered with Schedule 3 interliner.

Quilted seat cover: bottom: 100% cotton fabric FR treated; padding: FR resinated 100% polyester fiber "Valform" 200 gr/m²; top: Schedule 3 interliner. Dry clean only.

Fabric: Specifications: see sample attached. All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Safety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

*We suggest not to seat on armrests.
Dry clean only.*

MADE IN ITALY