

JAMES

Specifications

Mechanism (for bed only)

High resistance steel tube epoxy baked painted. Orthopedic bed with quality continental weld-mesh, fixed to the frame with springs. Seating with webbings. Opening and closing operations with two movements.

Mattress (for bed only)

Interior springing made of a 2 mm. diam. hardened steel; expanded polyurethane foam 27 Kg/m³; cover in 100% CO ecru fabric quilted with 100% PL 200 g/m²; sides in 100% CO ecru fabric quilted with mm. 5 foam; piping.

The mattress meets the requirement of BS 7177 : 1996 Specification for Resistance to ignition of Mattresses, Divans and Bed Bases.

Frame

Solid fir, poplar plywood.

Seat frame (for sofa without bed)

Solid fir, webbings.

Padding

Seat: Expanded polyurethane foam 35 Kg/m³; needle-punched thermo-fixed fiber 300 gr/m² covered with Schedule 3 interliner and 2,5 mm. foam combined interliner.

Back: Expanded polyurethane foam 25 Kg/m³ M CM and 25 Kg/m³ CM; needle-punched thermo-fixed fiber 300 gr/m² covered with Schedule 3 interliner and 2,5 mm. foam combined interliner.

Frame: Expanded polyurethane foam ELAST 65 Kg/m³ + 40 Kg/m³ CM, covered with needle-punched thermo-fixed fiber TL/S-C 200 gr/m² combined with Schedule 3 interliner and 2,5 mm. foam combined interliner.

Fabric

Specifications: see sample attached. All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Safety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

Legs

Steel tube epoxy baked painted (goffered silver color). Wooden legs upon request: veneered aluminum tube 30x30x2 mm., wengé, cherry or natural finish.

We suggest not to sit on armrests.

MADE IN ITALY