

LARRY

Specifications

Mechanism (or frame for sofa without bed)

High resistance steel tube epoxy baked painted. Orthopedic bed with quality continental weld-mesh, fixed to the frame with springs. Comfortable seating made with webbing. Opening and closing operations with one single movement (sofabed only).

Mattress (for bed only)

Interior springing made of a 2,20 mm. diam. hardened steel; CM expanded polyurethane foam 27 Kg/m3; cover in 100% CO ecru FR treated fabric quilted with FR 100% PL 200 g/m2 and "barrier" non woven support; sides in 100% CO ecru FR treated fabric quilted with mm. 5 foam; piping.

The mattress meets the requirement of BS 7177: 1996 Specification for Resistance to ignition of Mattresses, Divans and Bed Bases for "Medium Hazard" (Crib 5).

Frame

Back: high resistance steel tube epoxy baked painted. Armrests: solid fir, particle wood and poplar plywood. Headboard: solid fir and particle wood. Front panel (non-bearing) in particle wood.

Padding

Seat: expanded polyurethane foam CMHR 35 Kg/m³ and needle-punched thermo-fixed fiber 200 g/m² combined with Schedule 3 interliner and 2,5 mm. quilted interliner. **Back**: multiple density expanded polyurethane foam 25+40 Kg/m³ and needle-punched thermo-fixed fiber 200 g/m² combined with Schedule 3 interliner and 2,5 mm. quilted interliner. **Armrests**: expanded polyurethane foam 40 and 25 kg/m³, covered with Schedule 3 interliner combined with 200 g/m² PL fibre. **Frame**: expanded polyurethane foam 25 kg/m³ covered with Schedule 3 interliner combined with 200 g/m² PL fibre.

Pelmet (optional)

Chrome metal

Fabric

Specifications: see sample attached. All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Saety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

We suggest not to sit on armrests.

MADE IN ITALY

