

VIVIEN

Specifications

Mechanism or structure: High resistance steel tube epoxy baked painted. Orthopedic bed with quality continental weld-mesh, fixed to the frame with springs. Comfortable seating made with webbing. Opening and closing operations with one single movement (sofabed only).

Mattress standard (sofa bed only): Interior Bonnel springing made of a 2,20 mm Ø hardened steel; expanded polyurethane foam CM 27 Kg/m³; cover in 100% CO ecru FR treated fabric quilted with FR 100% PL 200 g/m² and non woven support; sides in 100% CO ecru FR treated fabric quilted with mm. 5 foam and non woven support; FR piping.

The mattress meets the requirement of BS 7177 : 2011 Specification for Resistance to ignition of Mattresses, Divans and Bed Bases for "Low Hazard".

Frame: solid fir and hardboard. Back: high resistance steel tube epoxy baked painted.

Padding: Seat: Expanded polyurethane foam 35 Kg/m³; needle-punched thermo-fixed fiber TLS/C 200 g/m² covered with Schedule 3 interliner and 2,5 mm. foam combined interliner.

Back: Expanded polyurethane foam 25 Kg/m³ M CM; needle-punched thermo-fixed fiber TLS/C 300 g/m² covered with Schedule 3 interliner and 2,5 mm. foam combined interliner.

Frame: Expanded polyurethane foam 40 Kg/m³ PCM, covered with needle-punched thermo-fixed fiber TLS/C 200 g/m² combined with Schedule 3 interliner and 2,5 mm. foam combined interliner.

Legs: metal epoxy baked painted.

Fabric: Specifications: see sample attached.

All fabrics meet the requirements of Schedule 4, Part I, "The Cigarette Test" of The Furniture and Furnishing (Fire) (Saety) Regulations 1988 (as amended) S.I. 1324, using the BS 5852: Part 1: 1979, Methods of test for the igniability by smokers' materials of upholstered composites for seating.

We suggest not to sit on armrests and headboard.

MADE IN ITALY